

# HCL-RC

## HYDROCHLORIC ACID LINED RAILCAR DISC

Oseco's HCL-RC (Hydrochloric Acid Lined Railcar Disc) has a large 4.75" outside diameter typically used in rubber lined tank cars. The disc is made with durable Ryton plastic and comes with standard fluoropolymer liners and gaskets adhered to both sides, giving maximum corrosion resistance.



DISC SHOWN FLOW SIDE UP



FLOW DIRECTION

[Buy Online Now](#)

### Oseco's HCL-RC railcar disc is designed for use with hydrochloric acid.

- 4.75" O.D.
- Rated to burst at 165 psig
- Designed primarily for rubber-lined tank cars used in Hydrochloric Acid service
- Consists of Ryton with Fluoropolymer linings and 1/32" Fluoropolymer gaskets secured to both sides
- Damage resistant
- Resistant to premature rupture during coupling and switching
- Excellent for highly corrosive environments
- "Fail-safe" design - a damaged or incorrectly installed HCL-RC will always burst at or below the stamped pressure
- Meets AAR Requirements

**Common Applications**  
Tank Cars

**Product Dimensions**  
Standard size fits threaded or bolted railroad tank car safety vent



## Related Products

**RUPTURE DISCS**  
HP-RC

Let us help you with all  
your pressure relief questions.  
Call us at **(800) 395-3475**  
or email us at **info@oseco.com**.  
**www.oseco.com**

