

MV-RF

METAL VENT-RECTANGULAR FLAT

Oseco's MV-RF (Metal Vent-Rectangular Flat) explosion vent is an all metal design (no fluoropolymer) using a stainless steel controlling membrane.

No holes or slits are visible, which makes the MV-RF vent excellent for applications, such as bag houses or bulk storage units, where product buildup may be a concern.

It may be exposed to system pressures up to 60% of stamped burst pressure. The MV-RF is also available with FDA-approved gaskets for use in sanitary service applications.



Buy Online Now

The MV-RF is Oseco's all metal explosion vent.

- Size Range 8" x 8" to 44" x 69"
- Set Pressure Range 0.2 psig to 10 psig (0.014 barg to 0.689 barg)
- Non-fragmenting design
- Higher vacuum resistance than any other flat vent design
- Materials of Construction: 316 Stainless Steel, Silicone Sealant, Neoprene Gasket (other gasket materials, including FDA gasket, are also available)
- Meets NFPA 61 and 68 regulations
- **1 Year Warranty**
- **2 Day Lead Time Available**

Common Applications

Applications Where Product Buildup is a Concern

Operating Ratio

60%

Burst Tolerance

+/-0.5psig over 2 psig,
+/-0.25 psig at or below 2 psig

Oseco MV-RF

Technical Specifications

MV-RF Explosion Vent Min/Max

| SIZE INCHES (mm) | RELIEF AREA in ² (m ²) | MIN psig (barg) | MAX psig (barg) |
|---|--|--------------------|--------------------|
| 8" x 8" (203mm x 203mm) | 54.0 (0.03) | 1.5 (0.10) | 10.0 (0.68) |
| 12" x 12" (305mm x 305mm) | 129.0 (0.08) | 1.4 (0.09) | 10.0 (0.68) |
| 12" x 18" (305mm x 457mm) | 196.0 (0.12) | 1.3 (0.09) | 5.0 (0.34) |
| 12" x 24" (305mm x 610mm) | 264.0 (0.17) | 1.3 (0.09) | 5.0 (0.34) |
| 16" x 18" (406mm x 457mm) | 266.0 (0.17) | 1.3 (0.09) | 5.0 (0.34) |
| 17.125" x 17.125" (435mm x 435mm) | 272.0 (0.17) | 1.3 (0.09) | 5.0 (0.34) |
| 18" x 24" (457mm x 610mm) | 405.0 (0.26) | 1.2 (0.08) | 5.0 (0.34) |
| 20" x 24" (508mm x 610mm) | 452.0 (0.29) | 1.2 (0.08) | 5.0 (0.34) |
| 18" x 28" (457mm x 711mm) | 474.0 (0.30) | 1.2 (0.08) | 5.0 (0.34) |
| 18" x 30" (457mm x 762mm) | 508.0 (0.32) | 1.2 (0.08) | 5.0 (0.34) |
| 24" x 24" (610mm x 610mm) | 546.0 (0.35) | 1.2 (0.08) | 5.0 (0.34) |
| 18" x 35" (457mm x 889mm) | 595.0 (0.38) | 1.2 (0.08) | 5.0 (0.34) |
| 18" x 36" (457mm x 914mm) | 612.0 (0.39) | 1.2 (0.08) | 5.0 (0.34) |
| 24" x 30" (610mm x 762mm) | 685.0 (0.44) | 1.1 (0.07) | 5.0 (0.34) |
| 24" x 36" (610mm x 914mm) | 825.0 (0.53) | 1.0 (0.06) | 5.0 (0.34) |
| 30" x 30" (762mm x 762mm) | 862.0 (0.55) | 1.0 (0.06) | 5.0 (0.34) |
| 20" x 48" (508mm x 1219mm) | 914.0 (0.58) | 1.0 (0.06) | 5.0 (0.34) |
| 27" x 36" (686mm x 914mm) | 931.0 (0.60) | 1.0 (0.06) | 5.0 (0.34) |
| 25" x 40" (635mm x 1016mm) | 957.0 (0.61) | 1.0 (0.06) | 5.0 (0.34) |
| 27" x 39" (686mm x 991mm) | 1010.0 (0.65) | 1.0 (0.06) | 5.0 (0.34) |
| 24" x 44" (610mm x 1118mm) | 1011.0 (0.65) | 1.0 (0.06) | 5.0 (0.34) |
| 25" x 43" (635mm x 1092mm) | 1030.0 (0.66) | 1.0 (0.06) | 5.0 (0.34) |
| 27" x 40" (686mm x 1016mm) | 1036.0 (0.66) | 1.0 (0.06) | 5.0 (0.34) |
| 30" x 36" (762mm x 914mm) | 1038.0 (0.66) | 1.0 (0.06) | 5.0 (0.34) |
| 24" x 47" (610mm x 1194mm) | 1081.0 (0.69) | 1.0 (0.06) | 5.0 (0.34) |
| 24" x 48" (610mm x 1219mm) | 1104.0 (0.71) | 0.9 (0.06) | 5.0 (0.34) |
| 27" x 43" (686mm x 1092mm) | 1115.0 (0.71) | 0.9 (0.06) | 5.0 (0.34) |

Related Products

SENSORS
SVT-03

HOLDERS
FRAMES
GASKETS

| SIZE INCHES (mm) | RELIEF AREA in ² (m ²) | MIN psig (barg) | MAX psig (barg) |
|---|--|-----------------|-----------------|
| 25" x 47" (635mm x 1194mm) | 1127.0 (0.72) | 0.9 (0.06) | 5.0 (0.34) |
| 25" x 49" (635mm x 1245mm) | 1176.0 (0.75) | 0.9 (0.06) | 5.0 (0.34) |
| 36" x 36" (914mm x 914mm) | 1251.0 (0.80) | 0.8 (0.05) | 5.0 (0.34) |
| 30" x 44" (762mm x 1118mm) | 1272.0 (0.82) | 0.8 (0.05) | 5.0 (0.34) |
| 27" x 52" (686mm x 1321mm) | 1351.0 (0.87) | 0.7 (0.04) | 5.0 (0.34) |
| 30" x 48" (762mm x 1219mm) | 1389.0 (0.89) | 0.7 (0.04) | 5.0 (0.34) |
| 38" x 38" (965mm x 965mm) | 1396.0 (0.90) | 0.7 (0.04) | 5.0 (0.34) |
| 27" x 58" (686mm x 1473mm) | 1509.0 (0.97) | 0.7 (0.04) | 5.0 (0.34) |
| 27.5" x 57.1" (698mm x 1450mm) | 1512.0 (0.97) | 0.7 (0.04) | 5.0 (0.34) |
| 36" x 44" (914mm x 1118mm) | 1533.0 (0.98) | 0.7 (0.04) | 5.0 (0.34) |
| 25" x 66" (635mm x 1676mm) | 1588.0 (1.02) | 0.6 (0.04) | 5.0 (0.34) |
| 27" x 66" (686mm x 1676mm) | 1719.0 (1.10) | 0.5 (0.03) | 5.0 (0.34) |
| 30" x 60" (762mm x 1524mm) | 1740.0 (1.12) | 0.5 (0.03) | 5.0 (0.34) |
| 42" x 44" (1067mm x 1118mm) | 1794.0 (1.15) | 0.5 (0.03) | 5.0 (0.34) |
| 44" x 44" (1118mm x 1118mm) | 1881.0 (1.21) | 0.5 (0.03) | 5.0 (0.34) |
| 44.5" x 44.5" (1130mm x 1130mm) | 1925.0 (1.24) | 0.5 (0.03) | 5.0 (0.34) |
| 36" x 60" (914mm x 1524mm) | 2097.0 (1.35) | 0.5 (0.03) | 5.0 (0.34) |
| 44" x 60" (1118mm x 1524mm) | 2573.0 (1.66) | 0.3 (0.02) | 5.0 (0.34) |
| 42" x 65" (1067mm x 1651mm) | 2660.0 (1.71) | 0.3 (0.02) | 5.0 (0.34) |
| 44" x 69" (1118mm x 1753mm) | 2962.0 (1.91) | 0.2 (0.01) | 5.0 (0.34) |

Let us help you with all
your pressure relief questions.

Call us at **(800) 395-3475**
or email us at info@oseco.com.

www.oseco.com

