

# OPR/OPK

OPR+/OPK+ RUPTURE DISC HOLDER

The Oseco OPR/OPK Rupture Disc Holder is designed to interface with multiple flange ratings. It is available with taps for an excess flow valve/pressure gauge and for the integral Flo-Tel+ rupture disc sensor.



**Oseco's OPR/OPK Holder is designed to bolt between standard ANSI flanges.**

- Designed for use with the reusable Flo-Tel+ sensor
- Minimizes inventory stocking requirements
- Standard material of construction 316 Series Stainless Steel
- Designed to meet ASME standards

## **Sizes**

1" - 12"

## **Common Applications**

Safety Relief Valve Isolation and Flanged Piping Systems



## Related Products

**ONE PIECE UNIT**  
OSECO SAFETY CARTRIDGE™

### RUPTURE DISCS

OPR+  
OPK+

### SENSORS

FLO-TEL+

## Certifications

**ASME UD**  
**CRN**  
**PED 2014/68/EU**

# Oseco OPR/OPK Holder Technical Specifications

## OPR/OPK Holder Dimensional Data

SIZE inches (metric)	ANSI RATING	O.D. (inches)	HEIGHT (inches)
1 DN 25	150/300/600	2.75	1.59
1.5 DN 40	150/300/600	3.63	1.67
2 DN 50	150/300/600	4.25	1.73
3 DN 80	150/300/600	5.75	2.17
4 DN 100	150/300	7.00	2.28
6 DN 150	150/300	9.75	2.91
8 DN 200	150	10.88	3.58
10 DN 250	150	13.25	4.14
12 DN 300	150	16.00	4.76

Let us help you with all  
your pressure relief questions.  
Call us at **(800) 395-3475**  
or email us at [info@oseco.com](mailto:info@oseco.com).

**[www.oseco.com](http://www.oseco.com)**

